SAFETY DATA SHEET

This SDS is prepared in accordance with OSHA 29 CFR 1910.1200



Section 1. Identification								
PRODUCT IDENTIFIER	PRO PERFORMANCE METAL TREATMENT			Code Mixture				
				CAS#	Mixture			
RECOMMENDED USE	SURFACE COATING PRODUCT							
	For Industrial use only. Not recommended for Medical Device or Drug use.				mergency	Chemtel		
MANUFACTURER / SUPPLIER	e9 TREATMENTS			(US/Canada		1-800-255-3924		
	159 Enterprise Parkway, Boerne, TX - 780				, ial)	+01-813-248-0585		
	P: 210-742-1051				,	101 010 2 10 0303		
Section 2. Information on Hazardo	us Ingredients							
HAZARD CLASSIFICATION	NOT CLASSIFIED AS HAZARDOUS ACCOR	DING TO OSHA HAZARD COM	MUNICATION STAN	DARD. 29 CF	R 1910.1200.			
LABEL ELEMENTS	SINGLE WORD NOT APPLICABLE							
	SYMBOLS	NOT APPLICABLE						
		NOT APPLICABLE						
HAZARD NOT OTHERWISE CLASSIFIED	NONE							
PRECAUTIONARY STATEMENTS	Store in a well-ventilated place. Keep Coc	I. Dispose of contents/contai	ner in accordance wit	h local/regio	onal /national/int	ernational regulations.		
Section 3. Composition / Informatio	n on ingredients							
DESCRIPTION	LIQUID							
INGREDIENT	C.A.S. NO.	% BY WT						
Fluoro Compound	Trade Secret*	< 5%						
METHYL NONAFLUOROBUTYL ETHER	163702-07-6	20-95%						
METHYL NONAFLUOROISOBUTYL ETHER	163702-08-7	20-95%						
* The specific chemical identity and/or percentag	ge of this material has been withheld as a trad	e secret						
Section 4. First Aid Measures								
INHALATION	Supply fresh air; consult doctor in case of	complaints.						
SKIN CONTACT	Immediately wash with water and soap and rinse thoroughly. If symptoms develop, seek medical help.							
EYE CONTACT	Rinse opened eye for several minutes under running water. Remove contacts if easy to do. If symptoms persist, seek medical help.							
INGESTION	Do not induce vomiting; call for medical help immediately. Rinse mouth with water.							
MOST IMPORTANT SYMPTONS AND	See Section 11.1 Information on Toxicological effects.							
EFFECTS								
INDICATION OF ANY IMMEDIATE	No further relevant information available.							
MEDICAL ATTENTION AND SPECIAL								
TREATMENT								
Section 5. Fire Fighting Measures								
SUITABLE/UNSUITABLE EXTINGUISHING	Non-combustible. Use fire extinguishing methods suitable to surrounding conditions.							
MEDIA	Foam.							
	Fire-extinguishing powder.							
	Carbon dioxide.							
SPECIFIC HAZARDS (IE HAZARDOUS		Formation of toxic gases is possible during heating or in case of fire.						
COMBUSTION PRODUCTS)	Hydrogen flouride (HF)							
	Carbon monoxide							
CDECIAL DEOTECTIVE ACTIONS FOR FIRE	Carbon dioxide	10.000			C 11			
SPECIAL PROTECTIVE ACTIONS FOR FIRE FIGHTERS	When fire fighting conditoins are severe a self contained, positive pressuure or pres	•						
	and protective covering for exposed area		ratus, buriker toat all	u pants, udfi	us arounu driils,	waist and iegs, late illask,		
Section 6. Accidental Release Meas								
PERSON PRECAUTIONS, PPE	Ensure adequate ventilation. Wear protection	ctive equipment. Keen upprot	tected persons away	Keep away				
	from ignition sources.							
ENVIRONMENTAL PRECAUTIONS	Do not allow to enter sewers/ surface or	ground water.						
	Prevent from spreading (e.g. by damming-in or oil barriers)							
		•	ewage system.					
METHODS & MATERIALS OF CONTAINMENT	Inform respective authorities in case of seepage into water course or sewage system. Contain call. Working from around the edges of the sail inward sover with hortonite vermiculity or commercially available.							
& CLEANING	Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible.							
	Clean up residue with an appropriate org							

Section 7. Handling and Storage							
PRECAUTIONS FOR SAFE HANDLING							
	Ensure good ventilation	on/exhaustion at the v	vorkplace. Do not breathe	thermal decomposition products.	Avoid skin contact with hot material. For		
	industrial or professio	nal use only. Store wo	ork clothes separately from	other clothing, food and tobacco	products. Avoid release to the environment.		
	Accordance to the contract of	idialna annoto (11	anima alamandi (d. 18. 18.	annaldan Caraldan oddin - 1	in mandank and manufation and another than 500		
					nis product can result in contamination of the		
	tobacco and/or smoke and lead to the formation of hazardous decomposition products.						
CONDITIONS FOR SAFE STORAGE	Keep away from heat						
CONDITIONS FOR SAFE STORAGE	Store in cool, dry conditions. Keep container tightly sealed. Only use containers compatible with the product. Store only in unopened original receptacles.						
	•		والمرام والمتعمد والمتعمد				
Castian O. Funcasina Cambuala/Dansan		with oxidising and at	idic materials as well as he	avy metal compunus.			
Section 8. Exposure Controls/Person	al Protection						
		CONTROL		1	¬		
COMPONENT	PEL/TWA/STEL	CONTROL PARAMETER	AGENCY	CAS			
METHYL NONAFLUOROBUTYL ETHER	TWA	750 ppm	AIHA	163702-07-6	7		
WETHTE NONAPLOOROBOTTE ETHER	TWA	750 ppiii	АПА	103702-07-0			
METHYL NONAFLUOROISOBUTYL ETHER	TWA	750 ppm	AIHA	163702-08-7			
INETITE HONAL EGORGISOSOTTE ETITEK	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	750 pp		100702 00 7			
	Due, dele en en entre 1	and nubnust out an	dust is booked 11	ا المالية الما	auh ausat		
VENTILATION /ENGINEERING CONTROLS		•	duct is heated. Use genera below relevant Exposure	Il dilution ventilation and/or local	exnaust		
				respiratory protection equipment.			
SKIN PROTECTION	Wear protective glove		•				
	The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.						
	Consider penetration times, rates of diffusion and the degradation of material when selecting gloves.						
MATERIAL OF GLOVES	Reinforced nitrile rubber. NBR						
	Suitable gloves not only depend on material, but also on manufacturing quality. Gloves should be						
	checked prior to use for good manufacturing quality.						
	Penetration time of glove material The exact breakthrough time of the glove material has to be found out by the						
	manufacturer of the protective glove and has to be observed.						
RESPIRATORY PROTECTION	Use suitable respirato	ry protective device ir	case of insufficient ventil	ation.			
THERMAL HAZARDS	Wear heat insulating gloves when handling hot material to prevent thermal burns.						
EYE PROTECTION	Wear safety glasses w	ith side shields.					
CLOTHING	Use protective suit.						
Section 9. Physical and Chemical Pro	perties						
Physical State and Appearance	Colorless liquid						
Odor	Ether-like						
Odor threshold	Not determined						
рН	Not applicable						
Melting/Freezing Point	-135º C						
Initial boiling point and boiling range	61° C						
Flash point	None						
Specific Gravity	1.5 [Ref Std: WATER=:	1]					
Evaporation rate	49 [Ref Std: BUOAC=1]					
Flammability (solid, gas)	None detected						
Upper/lower flammability or explosive limits:	None detected						
Vapor pressure	202 mmHg [@ 25 ºC]						
Vapor density	8.6 [Ref Std: AIR=1]						
Relative Density	1.5 g/ml						
Solubility (in H₂O)	< 12ppm						
Partition coefficient: n-octanol/water	3.9 [Details: 30 °C]						
Auto-ignition Temperature	405 ºC [Details: (ASTM	1 E659-84)]					
Decomposition temperature	Not Applicable						
Viscosity	0.6 centipoise [@ 23 º	pr 1					

Section 10. Stability and Reactivit	v Data							
INCOMPATIBILITY WITH VARIOUS								
SUBSTANCES	Avoid strong acid	s and strong bases.						
HAZARDOUS DECOMPOSITION PRODUCTS	At elevated temp	eratures: Carbon monoxide ;	carbon dioxide ; hydrogen flo	ouride ; Perfluoroisobutylene				
	Perflourinated Ac	Perflourinated Acid Flourides.						
	At extreme condi	At extreme conditions of heat toxic vapor, Gas, Particulate may be released.						
Section 11. Toxicological Informat	ion							
COMPONENT		Test	Control Pa	rameter				
METHYL NONAFLUOROBUTYL ETHER	Ora	al Rat LD 50	> 5000 n	ng/kg				
	Inhala	ation Rat LC50	> 100, 000	ppm 4H				
METHYL NONAFLUOROISOBUTYL ETHER	Ora	al Rat LD 50	> 5000 n	ng/kg				
	Inhala	ation Rat LC50	> 100, 000	ppm 4H				
INHALATION	No health effects	· · · · · · · · · · · · · · · · · · ·						
SKIN CONTACT		skin during product use is not						
EYE CONTACT		orary irritation on eyes with a	burning feeling, tearing, or re	edness.				
INGESTION	No known health							
ACUTE EFFECT ON HUMANS		No known health effects.						
CHRONIC EFFECT ON HUMANS	No known health	effects.						
Section 12. Ecological Information								
ECOTOXICITY		Test Organism		<u>Test Type</u>		Result		
	LC50 Fathead Mir	nnow, Pimephales promelas	96 h	ours Lethal Concentration 50%		> 7.9 mg/l		
	IC50 Green algae	, Selenastrum capricornutum	96 h	ours Inhibitory Concentration 5	50%	> 8.9 mg/l		
I	EC50 Water flea,	Daphnia magna	48 h	ours Effect Concentration 50%		> 10 mg/l		
Section 13. Disposal Consideration	ns							
WASTE INFORMATION	Send to an appro	Send to an approved waste facility.						
	All wastes must b	All wastes must be handled in accordance with local, state and federal regulations.						
	Do not allow prod	duct to reach sewage system	or any water course.					
Section 14. Transport Information	ı							
	Not regulated pe	r U.S. DOT, IATA or IMO.						
Section 15. Other Regulatory Info	rmation and Picto	grams						
US FEDERAL REGULATIONS	OSHA does not ha	OSHA does not have a formal Permissible Exposure Limit (PEL) for the 7100.						
	EPA Hazardous W	EPA Hazardous Waste Number (RCRA): Not regulated						
CHEMICAL INVENTORIES	Not Determined							
Section 16. Other Information								
NFPA Hazard Classification	Health: 0	Flammability: 0	Reactivity: 0	Special Hazaro	ds: None			
	in the workplace. use and are not in	Hazardous Material Identification System (HMIS*) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS* ratings are to be used with a fully implemented HMIS* program. HMIS* is a registered mark of the National Paint and Coatings Association (NPCA).						
HMIS Hazard Classification	Health: 1	Flammability: 0	Reactivity: 0	Protection: X	Protection: X - See PPE section.			
	hazards in the wo	Hazardous Material Identification System (HMIS* IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS* IV ratings are to be used with a fully implemented HMIS* IV program. HMIS* is a registered mark of the American Coatings Association (ACA).						
Notice to Reader								
To the best of our knowledge, the information of	contained herein is accu-	rate However neither the ab	ove named cumplier nor any	of its subsidiaries assumes and				
			ove numeu supplier nor any c	y its substitutives assurites ally				
liability whatsoever for the accuracy or complete			and an analysis and the second transfer of	والمادين المحجود والمادين والمادين والمادين				
Final determination of suitability of any materio	•	ty of the user. All materials n	* *	uriu snouia pe used with				

caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.