SAFETY DATA SHEET

This SDS is prepared in accordance with OSHA 29 CFR 1910.1200



						TEATM			
Section 1. Identification									
PRODUCT IDENTIFIER	PRO PREMIUM METAL TREATI	MENT		Code	Mixture				
				CAS#	Mixture				
RECOMMENDED USE	SURFACE COATING PRODUCT								
	For Industrial use only. Not recommended for Medical Device or Drug use.				nergency	Chemtel			
MANUFACTURER / SUPPLIER	e9 TREATMENTS					1-800-255-3924			
•	159 Enterprise Parkway, Boerne, TX - 78006				al)	+01-813-248-0585			
	P: 210-742-1051				,				
Section 2. Information on Hazardon	us Ingredients			<u> </u>					
HAZARD CLASSIFICATION	NOT CLASSIFIED AS HAZARDOUS ACCORDING	TO OSHA HAZAR	D COMMUNICATION STANDARD, 2	9 CFR 1910.1200.					
LABEL ELEMENTS	SINGLE WORD	NOT APPLICABLE							
	SYMBOLS	NOT APPLICABLE	≣						
	PICTOGRAMS	NOT APPLICABLE							
HAZARD NOT OTHERWISE CLASSIFIED	NONE								
PRECAUTIONARY STATEMENTS	Store in a well-ventilated place. Keep Cool. Disp	nose of contents/	container in accordance with local/r	regional /national/in	ternational re	gulations			
		rose or contents,	container in accordance with rocally	egronar / national/ in	iterriational re	- Guidelonisi			
Section 3. Composition / Informatio									
DESCRIPTION	LIQUID		1						
INGREDIENT	C.A.S. NO.	% BY WT							
Fluoro Compound	Trade Secret*	< 5%							
METHYL NONAFLUOROBUTYL ETHER	163702-07-6	20-95%							
METHYL NONAFLUOROISOBUTYL ETHER	163702-08-7	20-95%							
* The specific chemical identity and/or percentag	ge of this material has been withheld as a trade secr	ret							
Section 4. First Aid Measures									
INHALATION	Supply fresh air; consult doctor in case of comp	laints.							
SKIN CONTACT	Immediately wash with water and soap and rinse thoroughly. If symptoms develop, seek medical help.								
EYE CONTACT	Rinse opened eye for several minutes under running water. Remove contacts if easy to do. If symptoms persist, seek medical help.								
INGESTION	Do not induce vomiting; call for medical help immediately. Rinse mouth with water.								
MOST IMPORTANT SYMPTONS AND	See Section 11.1 Information on Toxicological effects.								
EFFECTS									
INDICATION OF ANY IMMEDIATE	No further relevant information available.								
MEDICAL ATTENTION AND SPECIAL									
TREATMENT									
Section 5. Fire Fighting Measures									
SUITABLE/UNSUITABLE EXTINGUISHING	Non-combustible. Use fire extinguishing metho	ds suitable to sur	rounding conditions.						
MEDIA									
	Fire-extinguishing powder.								
	Carbon dioxide.								
SPECIFIC HAZARDS (IE HAZARDOUS	Formation of toxic gases is possible during heat	ing or in case of	fire.						
COMBUSTION PRODUCTS)	Hydrogen flouride (HF)	J							
•	Carbon monoxide								
	Carbon dioxide								
SPECIAL PROTECTIVE ACTIONS FOR FIRE	When fire fighting conditions are severe and to	tal thermal decor	mposition of the product is possible	. wear full protective	e clothing, incl	uding helmet, self contained.			
FIGHTERS		d protective covering for expose							
	areas of the head.					<u> </u>			
Section 6. Accidental Release Meas	ures								
PERSON PRECAUTIONS, PPE	Ensure adequate ventilation. Wear protective e	quipment. Keep	unprotected persons away. Keep aw	/ay					
	from ignition sources.	•							
ENVIRONMENTAL PRECAUTIONS	Do not allow to enter sewers/ surface or ground water.								
	Prevent from spreading (e.g. by damming-in or oil barriers)								
		Inform respective authorities in case of seepage into water course or sewage system.							
			se or sewage system.						
METHODS & MATERIALS OF CONTAINMENT	Inform respective authorities in case of seepage	e into water cour		or commercially ava	ilahla				
		e into water cour of the spill inward	, cover with bentonite, vermiculite,						

Section 7. Handling and Storage RECAUTIONS FOR SAFE HANDLING Ensure good ventilation/exhaustion at the workplace. Do not breathe thermal decomposition products. Avoid skin contact with hot material. For industrial or professional use only. Store work clothes separately from other clothing, food and tobacco products. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of hazardous decomposition products. Keep away from heat and direct sunlight. CONDITIONS FOR SAFE STORAGE Store in cool, dry conditions. Keep container tightly sealed. Only use containers compatible with the product. Store only in unopened original receptacles. Do not store together with oxidising and acidic materials as well as heavy metal compunds. Section 8. Exposure Controls/Personal Protection CONTROL PEL/TWA/STEL AGENCY CAS COMPONENT PARAMETER METHYL NONAFLUOROBUTYL ETHER AIHA 163702-07-6 TWA 750 ppm METHYL NONAFLUOROISOBUTYL ETHER TWA 750 ppm AIHA 163702-08-7 VENTILATION /ENGINEERING CONTROLS Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, SKIN PROTECTION Wear protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Consider penetration times, rates of diffusion and the degradation of material when selecting gloves MATERIAL OF GLOVES Reinforced nitrile rubber, NBR Suitable gloves not only depend on material, but also on manufacturing quality. Gloves should be checked prior to use for good manufacturing quality. Penetration time of glove material The exact breakthrough time of the glove material has to be found out by the manufacturer of the protective glove and has to be observed. RESPIRATORY PROTECTION Use suitable respiratory protective device in case of insufficient ventilation. THERMAL HAZARDS Wear heat insulating gloves when handling hot material to prevent thermal burns. EYE PROTECTION Wear safety glasses with side shields. CLOTHING Select and use body protection to prevent contact when using the product in a manner that presents a higher potential for exposure. The following are recommended: Lab coat, Apron - polymer laminate. Section 9. Physical and Chemical Properties Physical State and Appearance Odor Ether-like Not determined Odor threshold Not applicable Melting/Freezing Point -135º C Initial boiling point and boiling range 61° C Flash point None Specific Gravity 1.5 [Ref Std: WATER=1] vaporation rate 49 [Ref Std: BUOAC=1] Flammability (solid, gas) None detected Upper/lower flammability or explosive limits: None detected Vapor pressure 202 mmHg [@ 25 ºC] Vapor density 8.6 [Ref Std: AIR=1] 1.5 g/ml Relative Density Solubility (in H₂O) < 12ppm 3.9 [Details: 30 °C] Partition coefficient: n-octanol/water 405 ºC [Details: (ASTM E659-84)] Auto-ignition Temperature Not Applicable Decomposition temperature 0.6 centipoise [@ 23 ºC] Viscosity

Percent Volatility

100%

Section 10. Stability and Reactivit	v Data								
INCOMPATIBILITY WITH VARIOUS	,								
SUBSTANCES	Avoid strong acids	Avoid strong acids and strong bases.							
HAZARDOUS DECOMPOSITION PRODUCTS	DECOMPOSITION PRODUCTS At elevated temperatures: Carbon monoxide; carbon dioxide; hydrogen flouride; Perfluoroisobutylene								
		Perflourinated Acid Flourides.							
	At extreme conditi	At extreme conditions of heat toxic vapor, Gas, Particulate may be released.							
Section 11. Toxicological Informat	tion								
2012001517		<u>.</u> . 1	0	. 7					
COMPONENT		Test	Control Para						
METHYL NONAFLUOROBUTYL ETHER		ral Rat LD 50	> 5000 mg	· -					
+	1	lation Rat LC50 ral Rat LD 50	> 100, 000 pp > 5000 mg						
METHYL NONAFLUOROISOBUTYL ETHER		lation Rat LC50	> 100, 000 pp	· -					
	IIIIIa	iation Rat LC50	> 100, 000 pp	ліі 4п					
INHALATION	No health effects a	ire expected.							
SKIN CONTACT		Contact with the skin during product use is not expected to result in significant irritation.							
EYE CONTACT		May cause temporary irritation on eyes with a burning feeling, tearing, or redness.							
INGESTION		No known health effects.							
ACUTE EFFECT ON HUMANS		No known health effects.							
CHRONIC EFFECT ON HUMANS		No known health effects.							
Section 12. Ecological Information									
ECOTOXICITY		Test Organism		Test Type	Result				
200100000	LC50 Fathead Min	now, Pimephales promelas	96 hou	urs Lethal Concentration 50%	> 7.9 mg/l				
		Selenastrum capricornutum		urs Inhibitory Concentration 50%	> 8.9 mg/l				
	EC50 Water flea, D	•		urs Effect Concentration 50%	> 10 mg/l				
Section 13. Disposal Consideration		aprilla magna	10 1100	and Effect content ation 50%	. 10g/				
WASTE INFORMATION		ed waste facility							
WASTE IN CHINATION		Send to an approved waste facility. All wastes must be handled in accordance with local, state and federal regulations.							
		Do not allow product to reach sewage system or any water course.							
Section 14. Transport Information		set to reach seriage system or an	y water course.						
		U.S. DOT, IATA or IMO.							
Section 15. Other Regulatory Info									
occion 13. Other negalatory into	That ion and Tictog	141113							
US FEDERAL REGULATIONS	OSHA does not ha	OSHA does not have a formal Permissible Exposure Limit (PEL) for the 7100.							
	EPA Hazardous Wa	EPA Hazardous Waste Number (RCRA): Not regulated							
CHEMICAL INVENTORIES	Not Determined								
Section 16. Other Information									
NFPA Hazard Classification	Health: 0	Flammability: 0	Reactivity: 0	Special Hazard	ls: None				
	workplace. These intended for use in	Hazardous Material Identification System (HMIS®) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).							
HMIS Hazard Classification	Health: 1	Flammability: 0	Reactivity: 0	Protection: X	tion: X - See PPE section.				
	workplace. These intended for use in	Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).							
Notice to Reader									
To the best of our knowledge, the information	contained herein is accure	ate However neither the above r	named sunnlier nor any of its subsidio	aries assumes anv					
liability whatsoever for the accuracy or comple			iamea supplier nor any oj its substata	nies assumes any					
Final determination of suitability of any materi			resent unknown hazards and should b	he used with					
		y oj trie user. Ali muteriuis muy pi		oc asca with					

caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.